

C.P. MOYEN CO.

Manufacturers of Adhesives, Coatings, Epoxies

847-673-6866
Fax 847-673-2812
Customer Service 847-673-6867

PRODUCT DATA: RS-3087 CEMENT

PRODUCT DESCRIPTION:

RS-3087 cement is a medium viscosity rubber resin cement. This cement has excellent adhesion to many substrates such as metal, paper, cloth, foam, felt, paperboard etc. This cement is a low VOC adhesive. It is recommended for spider to basket, gasket to cone, cone to basket, and screen to basket. It yields a tough but flexible adhesive.

Chemical Type	Rubber Resin	Flash Point	-4 F T.C.C.
Solids Content	31% \pm 2%	Color	Yellowish/Black
Specific Gravity	.90 \pm .01	Clean Up	Acetone
Weight per Gallon	7.5 \pm .1 lbs.		
Viscosity cps.	3500-5500*	Containers	5 gal., 50 gal.
* Brookfield Model LVT Spindle #4/60 rpm @ 77 F			

DIRECTIONS FOR USE

It can be applied with various methods including, roller, brush, squeeze bottle and various types of coating machinery. It can be used as a wet lay-up, heat reactivatable or solvent reactivatable adhesive. This adhesive has a very fast set up time.

STORAGE AND HANDLING

The shelf life is at least 6 months. For optimum shelf life of this product, store at temperatures of 60-80 F. Lower temperatures will cause increased viscosity of a temporary nature, whereas higher temperatures may have a permanent effect on viscosity.

WARNING: FLAMMABLE

Will Burn when exposed to spark or any flame source. Use only in a well ventilated area during application and until vapors subside.

All statements, technical information and recommendations contained herein are based on tests we believe to be accurate. The products are sold without warranty expressed or implied. The purchaser should make tests under your own conditions. The purchaser assumes all risk of use or handling, whether or not in accordance with any statements of the supplier. The supplier's liability, if any, for any action arising out of the material being supplied shall be limited to replacement of material.